



P110i

VALUE



P110i Card Printer

Basic specifications:

- » 30 sec/card full-colour, single-sided print speed
- » 100 card-capacity feeder
- » 16-digit LCD display
- » USB communication
- » CardSense™ single-card feed (optional)
- » Three-track HiCo/LoCo magnetic encoder, available in stripe up or stripe down (optional)

The P110i, Zebra's most affordable single-sided colour printer

The Zebra® P110i is a reliable, compact and easy-to-use card printer that delivers outstanding performance at a great price.

The P110i gives you versatility and cost-effectiveness for a wide variety of applications:

- » Employee ID and access cards
- » Student and faculty IDs
- » Membership cards
- » Personalised loyalty and gift cards

Zebra P110i advantages

Versatile: Print in full colour or monochrome. Choose automatic multi-card feed or CardSense single-card feed. Compact, sleek design lets you put the P110i just about anywhere.

Easy to use: Intuitive design reduces training costs. Blue touch points indicate user-touchable features. Translucent card cover allows you to see when card supply is running low. No-tools-necessary printhead replacement.

Innovative patent-pending technology: P110i uses high-strength plastics and advanced electronics for reduced size and weight and outstanding performance. Easy-to-replace Load-N-Go™ ribbon cartridge with integrated card cleaning roller features automatic setup and low ribbon warning indicator.

The Zebra P110i. Small printer, big statement.



**Card
Printer
Solutions**

P110i

Card Printer Product Specifications



General Specifications

- » Integrated card feeder and flipper
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-digit LCD display
- » Zebra® printer drivers for Windows® 2000 and Windows XP
- » Two year printer warranty
- » Two year (unlimited passes) printhead warranty

Printing

- » Colour dye sublimation or monochrome thermal transfer printing
- » 30 seconds per card full-colour single-sided (YMCKO)
- » 300 dpi (11.8 dots per mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with and without check digit
- » 2 of 5 and 2 of 5 Interleaved
- » UPC-A, EAN 8 and EAN 13
- » PDF-417 2-D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC composite
- » Card width/length: ISO CR-80, ISO 7810, 2.12" x 3.38" (54mm x 86mm)
- » Magnetic stripe ISO 7811
- » Smart card ISO 7816
- » Card thickness: 30 mil (0.76mm)
- » Card feeder capacity: 100 cards (0.76mm)
- » Card output hopper capacity: 45 cards (0.76mm)

Communications Interface

- » USB 1.1 (cable included)

Ribbon Specifications

- » Load-N-Go™ ribbon cartridge with integrated card-cleaning roller
 - » i Series ribbon information technology
 - » YMCKO: 200 cards/cartridge
 - » Monochrome: 1000 cards/cartridge in black, blue or white
- * for optimum printer performance use Genuine Zebra Supplies



Mechanical

- » Width: 7.9" (201mm)
- » Depth: 12.9" (328mm)
- » Height: 8.5" (216mm)
- » Weight: 9.5lb (4.3kg)

Electrical

- » 110~240 volts AC, 50~60Hz (auto-switching)
- » 16MB image memory standard
- » Approvals: FCC Class B, CE, UL and CUL

Environmental

- » Operating temperature: 60°F to 86°F (15°C to 30°C)
- » Operating humidity: 20% to 65% non-condensing
- » Storage temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage humidity: 20% to 70% non-condensing
- » Ventilation: free air

Options

- » Magnetic encoder (0.76mm cards only), three-track stripe up or down HiCo/LoCo (factory-installed)
- » CardSense™ single-feed kit
- » Cleaning kit (four cards for cleaning print engine and four for cleaning feeder)

Genuine Zebra Supplies

- » Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

www.zebracard.com



Zebra Technologies Corporation

ISO 9001
REGISTERED

An ISO 9001 registered company ©2005 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.
Part No. P110i-UK-11/05