



P310i

PERFORMANCE



P310i Card Printer

Basic Specifications:

- » 25 Seconds/Card Print Speed
- » Full Colour Single-Sided Card Printing
- » Parallel or USB Interface
- » 75 Card Capacity Feeder
- » *i* Series Printers require the use of TrueColours™ *i* Series ribbons for full colour printing

*i*series

Single-Sided Colour Card Printer Optimised for Fast Colour Printing

The Zebra P310i is an easy to use, reliable, single-sided card printer with convenient features to produce superior quality printing at an affordable price.

Use the P310i card printer to print:

- » Employee ID cards
- » Time and Attendance cards
- » Student ID's and Facilities Access Control cards
- » Club Membership and Loyalty cards

Zebra P310i Advantages

Advanced Colour Printing: Enhanced colour-processing firmware and new richer colour formulation

Reliable Operation: Based on the highly reliable, field-proven P310 print engine

***i* Series Intelligent Printing System:** Enhanced *i* Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Colour Optimisation
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation



**Card
Printer
Solutions**

P310i

Card Printer Product Specifications



General Specifications

- » High speed printing
- » 144 cards/hour for colour, single sided (YMCKO)
- » 900 cards/hour for resin black (K)
- » 2MB image memory standard
- » Windows® drivers for 98, ME, NT, 2000 and XP
- » Bi-directional driver communication
- » Two year printer warranty (varies by region)
- » Two year (unlimited passes) printhead warranty (varies by region)

Colour Printing

- » Colour dye sublimation or monochrome thermal transfer printing
- » 25 seconds per card full colour single sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm)
- » Card feeder capacity: 75 cards (30 mil)
- » Card output hopper capacity: 75 cards (30 mil)

Ribbon Specifications

- » i Series Printers require the use of i Series ribbons for full colour printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colours: black, red, blue, green, silver, gold, white and scratch-off grey
- » YMCKO: 200 & 330 cards/roll
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » Overlay varnishes: Clear and Hologram: 350 cards/roll



Communications Interface

- » Centronics Parallel (parallel cable included)
- » USB

Mechanical

- » Width: 12.4in (315mm)
- » Depth: 7.75in (198mm)
- » Height: 8.7in (220mm)
- » Weight: 13.4lbs (6.1kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

www.zebracard.com

*Optimised for use with Zebra media.



Zebra Technologies Corporation



An ISO 9001 registered company ©2003 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.
Part No. P310i-10/03

North America

**Zebra Technologies Corporation
Card Printer Solutions**
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

**Zebra Technologies Corporation
Card Printer Solutions**
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

**Zebra Technologies Corporation
Card Printer Solutions**
16 New Industrial Road
#05-03 Hudson TechnoCentre
Singapore 536204
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

**Zebra Technologies Corporation
Card Printer Solutions**
9800 NW 41St. Street
Suite 220, Doral, FL 33178, USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com