



# P330i

## PERFORMANCE



# P330i Card Printer

### Basic Specifications:

- » 25 Sec/Card Full Colour Print Speed
- » USB or USB with Built-in Ethernet
- » 100 card capacity feeder (220 high capacity feeder option)
- » LCD for immediate printer status
- » *iSeries* Printers require the use of TrueColours™ *iSeries* ribbons for full color printing

*iSeries*

### The New Face of Reliability

The next generation of the world's leading card printer, Zebra's P330i is the most powerful and flexible card printer in its class. Easy to use, this single-sided card printer produces reliable and high performance printing at an affordable price.

Use the P330i card printer for:

- » Corporate ID cards
- » Student and Faculty ID's and access control cards
- » Membership and Club cards for retail and warehouses
- » Hospital staff and patient ID's

### Zebra P330i Advantages

**Reliable Operation:** Newest generation of the highly reliable P330i series; Revolutionary angled card feeder design\*

**Powerful:** LCD display; Translucent card feeder and print viewing; Printhead bracket opens more than twice as wide as P310; Gentle open & close printhead latch

**Flexible:** 16 MB memory standard; Optional built-in Ethernet connectivity; Pass-through contact and contactless smart chip encoding options

*\*patent pending*



**Card  
Printer  
Solutions**

# P330i

## Card Printer Product Specifications



### General Specifications

- » High speed printing
- » 144 cards/hour for colour single-sided (YMCKO)
- » 16MB image memory standard
- » Windows® drivers for 2000 and XP
- » Bi-directional driver communication
- » Two years printer warranty
- » Two years (unlimited passes) printhead warranty

### Printing

- » Colour dye sublimation or monochrome thermal transfer printing
- » 25 seconds per card full colour single-sided (YMCKO)
- » 4 seconds/card for resin black (K)
- » 300 dpi (11.8 dots/mm) print resolution

### BarCodes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

### Card Specifications

- » Types: PVC, PVC Composite, Adhesive backed
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm) (+/- 10%)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

### Ribbon Specifications

- » i Series Printers require the use of i Series ribbons for full colour printing
- » Monochrome: 1500 (Black) & 1000 cards/roll
- » Monochrome colours: black, red, blue, green, silver, gold, white and scratch-off grey
- » YMCKO: 200 & 330 cards/roll
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » Overlay varnishes: Clear and Hologram: 350 cards/roll



### Communications Interface

- » USB 1.1 (cable included)
- » Built-in Ethernet Option

### Mechanical

- » Width: 18.2 in (462mm)
- » Depth: 9.4 in (239mm)
- » Height: 10.1 in (256mm)
- » Weight: 15.5 lbs (7.0kg)

### Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

### Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

### Options

- » Built-in Ethernet
- » Smart card contact and contactless (30 mil cards only)
- » Magnetic encoder (30 mil cards only), 3 track Hi-co and Lo-co
- » Cleaning supplies
- » High capacity feeder (220+ cards)
- » Service manual

[www.zebracard.com](http://www.zebracard.com)

*\*Optimized for use with Zebra media.*



Zebra Technologies Corporation



An ISO 9001 registered company ©2004 ZIH Corp.  
Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.  
Part No. P330i-09/04

#### North America

**Zebra Technologies Corporation  
Card Imaging Division**  
1001 Flynn Road  
Camarillo, CA 93012-8706  
USA  
Telephone: +1 805 579 1800  
Fax: +1 805 579 1808  
Toll free in US: 800 452 4056  
e-mail: [cards@zebra.com](mailto:cards@zebra.com)

#### Europe, Middle East, Africa

**Zebra Technologies Corporation  
Card Imaging Division**  
The Valley Centre, Gordon Road  
High Wycombe  
Buckinghamshire HP13 6EQ, UK  
Telephone: +44 870 241 1527  
Fax: +44 870 241 0765  
e-mail: [eurosales@zebra.com](mailto:eurosales@zebra.com)

#### Asia Pacific

**Zebra Technologies Corporation  
Card Imaging Division**  
16 New Industrial Road  
#05-03 Hudson TechnoCentre  
Singapore 536204  
Telephone: +65 6858 0722  
Fax: +65 6885 0836  
e-mail: [asiasales@zebra.com](mailto:asiasales@zebra.com)

#### Latin America

**Zebra Technologies Corporation  
Card Imaging Division**  
9800 NW 41st ST STE 220  
Doral, FL 33178, USA  
Telephone: +1 305 558 3100  
Fax: +1 305 558 8485  
e-mail: [latinsales@zebra.com](mailto:latinsales@zebra.com)