



P420i

PERFORMANCE



Dual-Sided Colour Card Printing is Easier and Faster Than Ever

The Zebra P420i card printer is a robust, dual-sided card printer with an LCD display and convenient easy-to-use features for producing high quality, personalised photo ID cards on-demand for high volume applications.

Use the P420i to print:

- » Employee/Student ID cards
- » Time and Attendance cards
- » Access Control cards

Zebra P420i Advantages

Advanced Colour Printing: Enhanced colour-processing firmware and new richer colour formulation

Reliable Operation: Full metal enclosure and field-proven reliable P310 print engine. Reject hopper separates cards that fail encoding prior to printing

i Series Intelligent Printing System: Enhanced i Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Colour Optimisation
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation

Basic Specifications:

- » 35 Seconds/Card Print Speed (YMCKOK)
- » Two-line LCD display with printer status and user commands
- » Full metal enclosure with viewing window
- » Full Colour or Monochrome Dual-Sided Card Printing
- » Parallel or USB Interface
- » 100 Card Capacity Feeder
- » i Series Printers require the use of TrueColours™ i Series ribbons for full colour printing

P420i Card Printer

*i*series



**Card
Printer
Solutions**

P420i

Card Printer Product Specifications



General Specifications

- » High speed printing
- » 102 cards/hour full colour, single-sided (YMCKOK)
- » 4MB image memory standard
- » Standard card flip over feature for dual-sided printing
- » Windows® drivers for 98, NT, 2000, ME, XP
- » Bi-directional driver communication
- » Two year printer warranty (varies by region)
- » Two year (unlimited passes) printhead warranty (varies by region)
- » Pass-code electronic lock

Colour Printing

- » Colour dye sublimation or monochrome thermal transfer printing
- » 35 seconds per card full colour single-sided (YMCKO/K)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811 » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm) to 60 mil (1.524mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Ribbon Specifications

- » i Series Printers require the use of i Series ribbons for full colour printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colours: black, red, blue, green, silver, gold white & scratch-off grey.
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » YMCKOK: 170 cards/roll
- » YMCKO: 200 & 330 cards/roll
- » Overlay varnishes: clear & hologram: 350 cards/roll



Communications Interface

- » Centronics Parallel (parallel cable included)
- » USB
- » Ethernet Option

Mechanical

- » Width: 20.90in (523mm)
- » Depth: 10.17in (253mm)
- » Height: 10.76in (269mm)
- » Weight: 27.5lbs (12.5kg)

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Ethernet
- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

www.zebracard.com

* Optimised for use with Zebra Media



Zebra Technologies Corporation



An ISO 9001 registered company ©2003 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.
Part No. P420-10/03

North America

**Zebra Technologies Corporation
Card Printer Solutions**
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

**Zebra Technologies Corporation
Card Printer Solutions**
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

**Zebra Technologies Corporation
Card Printer Solutions**
16 New Industrial Road
#05-03 Hudson TechnoCentre
Singapore 536204
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

**Zebra Technologies Corporation
Card Printer Solutions**
9800 NW 41St. Street
Suite 220, Doral, FL 33178, USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com